

## PicoYL-20

**YSL Photonics'** PicoYL-20 has a continuously tunable pulse duration from 200ps to 2ns and repetition rates from 30 kHz up to 1 MHz. The short pulse duration, high repetition rates combined with over 150kW peak power give high speed, permanent black/color marking on a variety of metals, thin film coating and thermal sensitive materials. The single mode beam quality picosecond pulses with over 150kW peak power open up a variety of micromachining applications such as SiC/Silicon cutting, resistor trimming and marking of transparent material. The laser is completely controlled via an industry standard digital interface with optional DB25 or RS-232.



### Features :

- Average Power ~20W
- Pulse Duration 200ps-2ns
- Peak Power 150kW
- Repetition Rate 30kHz-1000kHz
- Pulse Energy 100μJ@2ns or 30uJ@200ps
- $M^2 < 1.3$
- Burst Mode Function

### Applications :

- Silicon or SiC Dicing
- LED Sapphire Substrate Dicing
- Lion Ion Battery Foil Cutting
- Thin Film Solar Cell Scribing
- Metal Marking
- Chrome Vanadium Texturing
- Micromachining of Transparent materials

## Specifications :

Model	PicoYL-20
Wavelength	1030nm
Average Power	~20W
Repetition Rate	30-1000kHz
Power Stability	<2%
Pulse Energy	>30uJ@200ps or >100uJ@2ns
Peak Power	150kW
Pulse Duration	200ps-2ns
Switch On/Off Time	<5us
Beam Quality	$M^2 < 1.3$
Beam Diameter	5mm
Beam Divergence	<2mrad
Output Polarization	Linear Polarized
Trigger	SMA
Supply Power/Current	DC24V/8A
Dimensions	400mm*336mm*138mm
Control	RS232 or DB25

Optional 515nm output