

FemtoYL-6

YSL Photonics' FemtoYL-6 is the latest femtosecond fiber laser. It provides over 6W average power at 1035nm, with a pulse duration of 150fs and a repetition rate of 80MHz. FemtoYL-6 is a cost-effective fs fiber laser system that provides stable and clean short femtosecond pulses with an excellent beam quality and power stability. FemtoYL-6 is a great solution for applications of two-photon fluorescence microscopy and two-photon polymerization and etc.

Features:

- Average Power >6W
- Center wavelength 1035nm
- Pulse Duration 150fs
- Repetition Rate 80MHz

Applications:

- Two-Photon fluorescence microscopy
- Two-Photon polymerization
- OPO pumping
- Material micro-machining

TEL: +86 27 87204039

FAX: +86 27 87179217

Email: sales@yslphotonics.com





Specifications:

Model	FemtoYL-6
Iviouei	Fellito1E-0
Center Wavelength	1035nm
Total power	>6W
Repetition Rate	80MHz
Power Stability	<1%
Pulse Width	150fs
Beam Diameter	3mm
Beam Divergence	<1mrad
State of Polarization	Linear polarized(S)
Sync Output	SMA TTL pulse
Power Requirements	AC 220V/2A
Dimensions (L*W*H)	680mm*480mm*212mm
Control	RS232
Chiller	Water chiller



TEL: +86 27 87204039

FAX: +86 27 87179217

Email: sales@yslphotonics.com