

FemtoYL-UV-15

FemtoYL-UV is the latest industry femtosecond UV laser that based on fiber CPA technology. FemtoYL-UV has a ~300fs variable pulse duration in the wavelength of 343nm and a high average power up to 15W. Its pulse energy can up to 60μJ with a repetition rate of 1Hz-5MHz and an excellent beam pattern. FemtoYL-UV can provide stable 24*7 operation with a convenient maintenance, it is the best solution for preparation of display screen and the semiconductor industry.



Features:

- Central wavelength $343 \pm 5\text{nm}$
- Average power ~15W
- Pulse duration ~300fs
- Peak power 200MW
- Pulse energy 60μJ
- Beam quality $M^2 < 1.3$

Applications:

- OLED module cutting
- 5G circuit material cutting (LCP/MPI)
- FPC material cutting/drilling
- ITO drilling/scribing
- Semiconductor cutting/scribing
- Glass,sapphire drilling/scribing

Specifications:

Model	FemtoYL-UV-15
Central Wavelength	~343±5nm
Average Power	~15W
Pulse Duration	~300fs
Repetition Rate	1Hz-5MHz
Power Stability	<3%
Pulse Energy	60μJ
Peak Power	200MW
Beam Quality	M ² <1.3
Beam Diameter	~2mm(1m from output aperture)
Beam Divergence (Full Angle)	<2mrad(Defined by ISO-11146-1)
State of Polarization	Linear polarized(S)
Sync Output	SMA TTL pulse
Control	RS232
Power Requirements	AC 100V-240V50/60Hz Rated output>960W
Dimensions (L*W*H)	850mm*450mm*187.5mm

