

FemtoYL-Green-10

FemtoYL-Green-10 is the latest industry femtosecond laser that based on fiber CPA technology. FemtoYL-Green-10 has a 300fs variable pulse duration in the wavelength of 515nm and a high average power up to 10W. Its pulse energy can up to 15 μ J with a repetition rate of 1Hz-5MHz and an excellent beam pattern. FemtoYL-Green-10 can provide stable 24*7 operation with a convenient maintenance, it is the best solution for preparation of display screen and the semiconductor industry.



Features:

- Central wavelength ~515nm
- Average power ~10W
- Pulse duration ~300fs
- Peak power 40MW
- Pulse energy 15 μ J
- Beam quality $M^2 < 1.3$

Applications:

- OLED module cutting
- 5G circuit material cutting (LCP/MPI)
- FPC material cutting/drilling
- ITO drilling/scribing
- Semiconductor cutting/scribing
- Glass, sapphire drilling/scribing

Specifications:

Model	FemtoYL-Green-10
Central Wavelength	515nm
Average Power	10W
Pulse Duration	~300fs
Repetition Rate	1Hz-5MHz
Power Stability	<2%
Pulse Energy	15μJ
Peak Power	40MW
Beam Quality	M ² <1.3
Beam Diameter	~3mm(1m from output aperture)
Beam Divergence (Full Angle)	<2mrad(Defined by ISO-11146-1)
State of Polarization	Linear polarized(S)
Sync Output	SMA TTL pulse
Control	RS232
Power Requirements	AC 100V-240V50/60Hz Rated output>960W
Dimensions (L*W*H)	680mm*410mm*187.5mm

